

S5-GR1P(0.7-3)K-M

Solis Mini Series Inverters



360 degree

Features:

- Max. efficiency 97.1%
- Max. input current **14A**
- Complies with all state network requirements
- Integrate with adjustable Volt-Watt and Volt-Var function
- DRM integrated, fully comply with AS/NZS 4777.2:2020
- Built-in DC-PV2 Switch (optional), comply with AS/NZS 5033 requirements
- Support 24h consumption monitoring with a smart meter
- Super high frequency switching technology
- Precise MPPT algorithm
- Integrated Export Power Manager (EPM)
- Compact and lightweight
- Voltage active power and reactive power



Model:

S5-GR1P0.7K-M	S5-GR1P1K-M
S5-GR1P1.5K-M	S5-GR1P2K-M
S5-GR1P2.5K-M	S5-GR1P3K-M

Datasheet

Model Name	S5-GR1P0.7K-M	S5-GR1P1K-M	S5-GR1P1.5K-M	S5-GR1P2K-M	S5-GR1P2.5K-M	S5-GR1P3K-M
Input DC						
Recommended max. PV power	0.93 kW	1.33 kW	2 kW	2.6 kW	3.33 kW	4 kW
Max. input voltage			600 V			
Rated voltage		200 V			330 V	
Start-up voltage		60 V			90 V	
MPPT voltage range		50-500 V			80-500 V	
Max. input current			14 A			
Max. short circuit current			22 A			
MPPT number/Max. input strings number			1/1			
Output AC						
Rated output power	0.7 kW	1 kW	1.5 kW	2 kW	2.5 kW	3 kW
Max. apparent output power	0.7 kVA	1 kVA	1.5 kVA	2 kVA	2.5 kVA	3 kVA
Max. output power	0.7 kW	1 kW	1.5 kW	2 kW	2.5 kW	3 kW
Rated grid voltage			1/N/PE, 230 V			
Rated grid frequency			50 Hz			
Rated grid output current	3.0 A	4.3 A	6.5 A	8.7 A	10.9 A	13 A
Max. output current	4.4 A	5.2 A	8.1 A	10.5 A	13.3 A	15.7 A
Power Factor			>0.99 (0.8 leading - 0.8 lagging)			
THDi			<3%			
Efficiency						
Max. efficiency	96.6%		96.6%	97.1%		97.1%
EU efficiency	95.3%		95.4%	96.6%		96.7%
Protection						
DC reverse-polarity protection			Yes			
Short circuit protection			Yes			
Output over current protection			Yes			
Surge protection			Yes			
Grid monitoring			Yes			
Anti-islanding protection			Yes			
Temperature protection			Yes			
Integrated DC switch			Optional (PV2 Switch)			
General Data						
Dimensions (W*H*D)			310*373*160 mm			
Weight		7.4 kg			7.7 kg	
Topology			Transformerless			
Self consumption (night)			<1 W			
Operating ambient temperature range			-25 ~ +60°C			
Relative humidity			0-100%			
Ingress protection			IP65			
Cooling concept			Natural convection			
Max. operation altitude			2000 m			
Grid connection standard		AS/NZS 4777.2:2020, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530				
Safety/EMC standard			IEC 62109-1/-2, IEC 61000-6-1/-2/-3/-4			
Features						
DC connection			MC4 connector			
AC connection			Quick connection plug			
Display			LCD			
Communication			RS485, Optional: Wi-Fi, GPRS			
Country of manufacture			China			