
MAXEON 3 SOLAR PANEL

380-400 W | Up to 22.6% Efficient





White backsheet, silver frame

More Lifetime Energy

Designed to maximise energy generation through leading efficiency, enhanced performance in high temperatures, and higher energy conversion in low-light conditions like mornings, evenings and cloudy days.

Uncompromising Durability

Engineered to power through all types of weather conditions with crack-resistant cells and reinforced connections that protect against fatigue and corrosion, to an electrical architecture that mitigates the impact of shade and prevents hot-spot formation.



Superior Sustainability

Clean ingredients, responsible manufacturing, and lasting energy production for 40 years make SunPower Maxeon panels the most sustainable choice in solar.



The Industry's Longest Warranty

SunPower Maxeon panels are covered by a 40-year warranty¹ backed by extensive third-party testing and field data from more than 33 million panels deployed worldwide.

Product and power coverage 40 Years
Year 1 minimum warranted output 98.0%
Maximum annual degradation 0.25%




MAXEON 3 POWER: 380–400 W | EFFICIENCY: Up to 22.6%

Electrical Data			
	SPR-MAX3-400-	SPR-MAX3-390-	
	COM	COM	COM
Nominal Power (Pnom) ²	400 W	390 W	380 W
Power Tolerance	+5/0%	+5/0%	+5/0%
Panel Efficiency	22.6%	22.1%	21.5%
Rated Voltage (Vmpp)	66.0 V	64.5 V	63.1 V
Rated Current (Impp)	6.07 A	6.05 A	6.02 A
Open-Circuit Voltage (Voc)	75.4 V	75.3 V	75.2 V
Short-Circuit Current (Isc)	6.57 A	6.55 A	6.54 A
Max. System Voltage	1000 V IEC		
Maximum Series Fuse	20 A		
Power Temp Coef.	−0.27% / °C		
Voltage Temp Coef.	−0.236% / °C		
Current Temp Coef.	0.058% / °C		

Warranties, Certifications and Compliance		
Standard Tests ³	IEC 61215, IEC 61730	
Quality Management Certs	ISO 9001:2015, ISO 14001:2015	
Ammonia Test	IEC 62716	
Desert Test	IEC 60068-2-68, MIL-STD-810G	
Salt Spray Test	IEC 61701 (maximum severity)	
PID Test	1000 V: IEC 62804	
Available Listings	TUV	
IFLI Declare Label	First solar panel labeled for ingredient transparency and LBC-compliance. 4	
Cradle to Cradle Certified TM Bronze	First solar panel line certified for material health, water stewardship, material reutilization, renewable energy & carbon management, and social fairness. ⁵	
Green Building Certification Contribution	Panels can contribute additional points toward LEED and BREEAM certifications.	
EHS Compliance	RoHS, OHSAS 18001:2007, Recycle Scheme, REACH SVHC-163	

Operating Condition And Mechanical Data		
Temperature	-40°C to +85°C	
Impact Resistance	25 mm diameter hail at 23 m/s	
Solar Cells	104 Monocrystalline Maxeon Gen 3	
Tempered Glass	High-transmission tempered anti-reflective	
Junction Box	IP-68, Stäubli (MC4), 3 bypass diodes	
Weight	19 kg	
Max. Load ⁶	Wind: 2400 Pa, 244 kg/m² front & back Snow: 5400 Pa, 550 kg/m² front	
Frame	Class 2 silver anodized	











Please read the safety and installation instructions. Visit www.sunpower.maxeon.com/int/PVInstallGuideIEC. Paper version can be requested through techsupport.ROW@maxeon.com.

- 1 40-year warranty is not available in all countries or all installations and requires registration, otherwise our 25-year warranty applies. Service availability varies by country and installation
- 2 Standard Test Conditions (1000 W/m² irradiance, AM 1.5, 25° C). NREL calibration Standard: SOMS current, LACCS FF and Voltage.
- 3 Class C fire rating per IEC 61730.
- 4 Maxeon DC panels first received the International Living Future Institute Declare Label in 2016.
- 5 Maxeon DC panels are Cradle to Cradle Cradle Certified™ Bronze Bronze -

www.c2ccertified.org/products/scorecard/e-series_xseries_solar_panels_-

- _sunpower_corporation. Cradle to Cradle Certified™ is a certification mark licensed by the Cradle to Cradle Products Innovation Institute.
- 6 Safety factor 1.5 included.

