

SPECIFICATION

Model	Powercube H3-7	Powercube H3-10	Powercube H3-14	Powercube H3-17
Usable Energy	7.10kWh	10.65kWh	14.20kWh	17.76kWh
Nominal Capacity	37Ah	37Ah	37Ah	37Ah
Nominal Voltage	192V	288V	384V	480V
Max.Continuous discharge power	7kW	10kW	14kW	17kW
Max.Continuous charge power	7kW	10kW	14kW	17kW
Net Weight	120Kg	155Kg	190Kg	235Kg
Dimension[W*D*H]	1040*600*526	1040*600*526	1040*600*526	1218*600*526
Protection Level	IP65	IP65	IP65	IP65
Catendar Life ^[1]	6000 Cycles	6000 Cycles	6000 Cycles	6000 Cycles
Charging temp.range	0 ~ 45°C	0 ~ 45°C	0 ~ 45°C	0 ~ 45°C
Discharging temp.range	-10 ~ 45°C	-10 ~ 45°C	-10 ~ 45°C	-10 ~ 45°C
Internal battery module	H3	H3	H3	H3
Module Connection	Series	Series	Series	Series
Module Number	2	3	4	5
Commnication	CAN	CAN	CAN	CAN
Warranty	10 year	10 year	10 year	10 year

[1] Test conditions:0.2C Charging/Discharging,@25°C,80% Dod